

Spec (in)	Weight (lb/ft)	Outside Diameter (in)	Wall Thickness (in)	Type of pipe finishing						
				J55/K55	M65	L80/C95	N80	C90/T95	P110	Q125
4 1/2	9.5	4.5	0.205	PS	PS	---	---	---	---	---
	10.5	4.5	0.224	PSB	PSB	---	---	---	---	---
	11.6	4.5	0.25	PSLB	PLB	PLB	PLB	PLB	PLB	---
	13.5	4.5	0.29	---	PLB	PLB	PLB	PLB	PLB	---
15.1	4.5	0.37	---	---	---	---	---	PLB	PLB	
5	11.5	5	0.22	PS	PS	---	---	---	---	---
	13.0	5	0.253	PSLB	PLB	PLB	PLB	PLB	---	---
	15.0	5	0.296	PSLB	PLB	PLB	PLB	PLB	---	---
	18.0	5	0.396	---	PLB	PLB	PLB	PLB	PLB	PLB
	21.2	5	0.437	---	PLB	PLB	PLB	PLB	PLB	PLB
	23.2	5	0.478	---	---	PLB	PLB	PLB	PLB	PLB
	24.1	5	0.5	---	---	PLB	PLB	PLB	PLB	PLB
5 1/2	14.0	5.5	0.224	PS	PS	PS	---	---	---	---
	15.5	5.5	0.275	PSLB	PSLB	---	---	---	---	---
	17.0	5.5	0.304	PSLB	PLB	PLB	PLB	PLB	PLB	PLB
	20.0	5.5	0.361	---	PLB	PLB	PLB	PLB	PLB	---
	23.0	5.5	0.415	---	PLB	PLB	PLB	PLB	PLB	PLB
	26.8	5.5	0.5	---	---	---	---	P	---	---
	29.7	5.5	0.562	---	---	---	---	P	---	---
6 5/8	20.0	6.625	0.228	PSLB	PSLB	---	---	---	---	---
	24.0	6.625	0.352	PSLB	PSLB	PLB	PLB	PLB	PLB	---
	28	6.625	0.417	---	PLB	PLB	PLB	PLB	PLB	---
	32.0	6.625	0.475	---	---	---	PLB	PLB	PLB	PLB
7	17.0	7	0.231	PS	---	---	---	---	---	---
	20.0	7	0.272	PS	PS	---	---	---	---	---
	23.0	7	0.371	PSLB	PLB	PLB	PLB	PLB	---	---
	26.0	7	0.362	PSLB	PLB	PLB	PLB	PLB	PLB	---
	29.0	7	0.408	---	PLB	PLB	PLB	PLB	PLB	---
	32.0	7	0.453	---	PLB	PLB	PLB	PLB	PLB	---
	35.0	7	0.498	---	---	PLB	PLB	PLB	PLB	PLB
38.0	7	0.54	---	---	PLB	PLB	PLB	PLB	PLB	
7 5/8	24.0	7.625	0.3	---	---	---	---	---	---	---
	26.4	7.625	0.328	PSLB	PSLB	PLB	PLB	PLB	---	---
	29.7	7.625	0.375	---	PSB	PLB	PLB	PLB	PLB	---
	33.7	7.625	0.43	---	---	PLB	PLB	PLB	PLB	---
	39.0	7.625	0.5	---	---	PLB	PLB	PLB	PLB	PLB
	42.8	7.625	0.562	---	---	PLB	PLB	PLB	PLB	PLB
45.3	7.625	0.595	---	---	PLB	PLB	PLB	PLB	PLB	
8 5/8	24.0	8.625	0.264	PS	PS	---	---	---	---	---
	28.0	8.625	0.304	PS	PS	---	---	---	---	---
	32.0	8.625	0.352	PSLB	PSLB	---	---	---	---	---
	36.0	8.625	0.4	PSLB	PSLB	PLB	PLB	PLB	---	---
	40.0	8.625	0.45	---	PLB	PLB	PLB	PLB	PLB	---
	44.0	8.625	0.5	---	---	PLB	PLB	PLB	PLB	---
	49.0	8.625	0.557	---	---	PLB	PLB	PLB	PLB	PLB
9 5/8	32.3	9.625	0.312	---	---	---	---	---	---	---
	36.0	9.625	0.352	PSLB	PSLB	---	---	---	---	---
	40.0	9.625	0.395	PSLB	PSLB	PLB	PLB	PLB	---	---
	43.5	9.625	0.435	---	PLB	PLB	PLB	PLB	PLB	---
	47.0	9.625	0.472	---	---	PLB	PLB	PLB	PLB	PLB
	53.5	9.625	0.545	---	---	PLB	PLB	PLB	PLB	PLB
58.4	9.625	0.595	---	---	PLB	PLB	PLB	PLB	---	
10 3/4	32.75	10.75	0.279	---	---	---	---	---	---	---
	40.5	10.75	0.35	PSB	PSB	---	---	---	---	---
	45.5	10.75	0.40	PSB	PSB	---	---	---	---	---
	51.0	10.75	0.45	PSB	PSB	PSB	PSB	PSB	PSB	PSB
	55.5	10.75	0.495	---	PSB	PSB	PSB	PSB	PSB	PSB
	60.7	10.75	0.545	---	---	---	---	PSB	PSB	PSB
	65.7	10.75	0.595	---	---	---	---	PSB	PSB	PSB
11 3/4	42.0	11.75	0.333	---	---	---	---	---	---	---
	47.0	11.75	0.375	PSB	PSB	---	---	---	---	---
	54.0	11.75	0.435	PSB	PSB	---	---	---	---	---
	60.0	11.75	0.489	PSB	PSB	---	---	---	---	---
	65.0	11.75	0.534	---	---	---	---	---	---	---
71.0	11.75	0.582	---	---	---	---	---	---	---	
13 3/8	48.0	13.375	0.330	---	---	---	---	---	---	---
	54.5	13.375	0.380	PSB	PSB	---	---	---	---	---
	61.0	13.375	0.430	PSB	PSB	---	---	---	---	---
	68.0	13.375	0.480	PSB	PSB	---	---	---	---	---
	72.0	13.375	0.514	---	---	---	---	---	---	---
16	65.0	16.0	0.375	---	---	---	---	---	---	---
	75.0	16.0	0.438	PSB	PSB	---	---	---	---	---
	84.0	16.0	0.495	PSB	PSB	---	---	---	---	---
	109.0	16.0	0.656	P	---	P	P	---	P	P
18 5/8	87.5	18.625	0.435	PSB	PSB	---	---	---	---	
20	94.0	20.0	0.438	PSLB	PSLB	---	---	---	---	---
	106.5	20.0	0.500	PSLB	PSLB	---	---	---	---	---
	133.0	20.0	0.635	PSLB	---	---	---	---	---	---

P: Plain End; S: Short Round Thread; L: Long Round; B: Buttress Thread.